

H&K International

High Capacity Freezer-Refrigerator Combo (HCFRC18.01P)

Weekly maintenance tasks

RF 10 W01 Clean Unit

Quarterly maintenance tasksRF 10 Q01 Clean Condenser
Coil & Check
Door Gasket

△ Hazards

These icons alert you to a possible risk of personal injury.

▨ Equipment alerts

Look for this icon to find information about how to avoid damaging the equipment while doing a procedure.

★ Tips

Why	The unit must be cleaned weekly to ensure proper operation.	
Time required	5 minutes to prepare	15 minutes to complete
Time of day	Evening after closing	For 24-hour restaurants: during slow period
Hazard icons	 Electricity	

Tools and supplies Soft bristled brush



- 1 Turn off unit**
Press and hold right lower button of controller for 5 seconds to turn off the unit.



- 4 Wipe down Inside of Drawers**
Wipe down inside of drawers with a towel and sanitizing solution.




- 2 Remove items from unit**
Place remaining items into walk-in cooler while cleaning unit.



- 5 Turn on unit**
Press and hold right lower button of controller for 5 seconds to turn on the unit. Allow to reach operating temperature.



- 3 Remove dividers**
Wash in sink with mild soap and sanitize with a solution of McD Sanitizer (HCS). Allow accessories to air dry.



- 6 Re-fill unit with products**
Re-fill the unit with the items from the walk-in cooler.



Clean Condenser Coil & Check Drawer Gaskets

Quarterly

RF 10 Q01

Why The condenser coil must be cleaned regularly to ensure the unit operates at peak performance. The drawer gaskets condition must be checked to ensure the unit is sealed properly. Failure to do so could result in food product quality risks, premature refrigeration failure, additional energy usage, and voiding of warranty.

Time required 10 minutes to prepare 15 minutes to complete

Time of day Evening after closing For 24-hour restaurants: during slow period

Hazard icons  Electricity

Tools and supplies Soft bristled brush



1 Turn off unit

Press and hold right lower button of controller for 5 seconds to turn off the unit.



4 Replace slotted panel

Reinstall panel by aligning tabs with slots on each side of condenser housing. Push panel in and down until secure.



Tip Make sure to check that the panel is tightly secured.



2 Remove slotted panel

Lift panel up to clear tabs at each side of panel.



5 Check Drawer gaskets

Check to see if door gasket is broken. If the door gasket is broken, and cannot seal the cabinet properly, please call **800-521-3987** to order replacement gasket.



3 Clean Condenser Coil

Using a soft bristled brush remove any dirt present on the coil.



Tip Make sure to brush with the direction of the fins.



6 Turn on unit

Press and hold right lower button of controller for 5 seconds to turn on the unit.



