

H&K International High Capacity Wall Freezer (HCWF1, Single-Wide)

Weekly maintenance tasks

RF 06 W1 Clean Unit

Quarterly maintenance tasksRF 06 Q1 Clean Condenser
Coil**Annual maintenance tasks**

RF 06 A1 Inspect Gasket

**△ Hazards**



These icons alert you to a possible risk of personal injury.

▨ Equipment alerts

Look for this icon to find information about how to avoid damaging the equipment while doing a procedure.

★ Tips

Look for this icon to find helpful tips about how to do a procedure.

Why	The unit must be cleaned weekly to ensure proper operation.	
Time required	5 minutes to prepare	15 minutes to complete
Time of day	Evening after closing	For 24-hour restaurants: during slow period
Hazard icons	 Electricity	 Fall Hazard

Tools and supplies



Clean cloth



Ladder

Procedure

- 1 Turn off unit**
Turn off the power switch.



- 4 Plug in unit and turn on**
Plug the unit back into the same wall receptacle and turn on the power switch. Allow unit to reach operating temperature.



- 2 Remove items from unit**
Place remaining items into walk-in freezer while cleaning unit.

- 3 Wipe down unit**
Remove bottom shelf. Wipe down inside and outside of unit with a clean sanitized towel. Clean bottom shelf. Clean doors and gaskets.



- 5 Re-fill unit with products**
Re-fill the unit with the items from the walk-in

Why The condenser coil must be cleaned regularly to ensure the unit operates at peak performance. Failure to do so could result in food product quality risks, premature refrigeration failure, additional energy usage, and voiding of warranty.

Time required 10 minutes to prepare 15 minutes to complete

Time of day Evening after closing For 24-hour restaurants: during slow period

Hazard icons  Electricity  Fall Hazard

Tools and supplies




Soft Bristled Brush



Ladder

Procedure

1 Turn off unit
Turn off the power switch.
Remove any food equipment from underneath freezer.
Cover fryers
 Electricity




2 Remove panel
Lift panel up to clear tabs.




3 Remove Panel
Slide panel away from unit.




4 Clean Condenser Coil
Using a soft bristled brush, remove any dirt present on the coil.
 **Tip**
Make sure to brush with the direction of the fins.





5 Replace panel
Replace panel by aligning all hooks with slots in front of unit. Slide panel down.
 **Tip**
Make sure to check that the panel is tightly secured.



6 Turn on unit
Turn on the power switch
 Electricity



Why	The door gasket must be inspected to ensure proper cooling of freezer	
Time required	5 minutes to prepare	5 minutes to complete
Time of day	Evening after closing	For 24-hour restaurants: during slow period
Hazard icons	 Electricity	 Fall Hazard

Tools and supplies



Ladder

Procedure

- 1 Open Door**
 Inspect entire perimeter of door gasket, including corners, for any tears in gasket. If torn, contact **H&K Service at 800-788-2445** to order replacement.

